

PRO RX-14 SERIES

Interactive Flat Panel Display



	Android 14.0
	RAM 8 GB
	ROM 128 GB


PRODUCT MAY VARY FROM THE ACTUAL PRODUCT



20 Touch Points



5.0 Bluetooth version



Octa-core



Eye protection, lock screen, touch lock and other tools.



20Wx2(INBUILT)

PROMARK INTERACTIVE PANEL

DISPLAY

Active Screen Size	65"	75"	86"
Response time	<4ms	<4ms	<4ms
Aspect ratio	16:9	16:9	16:9
Max Visual Area	1429(H) × 804(V) mm	1651(H) × 929(V) (mm)	1897(H) × 1067(V)mm
Resolution	3840 (H) × 2160 (V)	3840 (H) × 2160 (V)	3840 (H) × 2160 (V)
Pixel pitch	0.372×0.372mm	0.42975 (W) × 0.42975(H)	0.4935×0.4935mm
Frequency	120Hz	120Hz	120Hz
Display Color	1.07B(10bit)	1.07B(10bit)	1.07B (10bit)
Contrast ratio (Typ)	30000:1	30000:1	30000:1
Viewing Angle	178°(H/V)	178°(H/V)	178°(H/V)
Back Light source	DLED	DLED	DLED
Brightness (Typ)	450cd/m2	500cd/m2	600cd/m2
Life span	1,20,000 hours	1,20,000 hours	1,20,000 hours

TOUCH & WRITING

Touch Technology	IR Touch
Supported system	Windows10/Windows8/Windows7/Windows XP/Android/Linux/Mac OS X/Chrome
Touch points	20 points touch
Input mode	Finger, Passive IR pen

SPEAKER

Speaker Max.Power Output	20Wx2(INBUILT)
Soundtrack	2.0

PROMARK INTERACTIVE PANEL

SYSTEM

System version	Android 14.0
Working frequency	1.2GHZ
CPU	8-Core A55
GPU	Octa-core
RAM	8GB
ROM	128GB

BLUETOOTH

Bluetooth version	5.0
Operation frequency	2.4GHz
Operation distance	0~10m
Remark	Built-in Bluetooth

Wi-Fi

Version	802.11ac/b/g/n/a
Operation frequency	2.4GHz/5GHz
Operation distance	0~10m
Remark	Built-in Wi-Fi mode

FRONT INTERFACE

USB 3.0	3
HDMI IN	1
TOUCH OUT	1
TYPEC	1
Keys	Switch,Home,Screen Down,Record,Touch Lock,Settings

PROMARK INTERACTIVE PANEL

ONBOARD INTERFACE

TF CARD	1
USB 3.0	1
USB 2.0	1
TOUCH	1
HDMI IN	2
HDMI OUT	1
VGA	1
AUDIO IN	1
DP IN	1
RS232	1
RJ45 OUT	1
MIC IN	1
AUDIO OUT	1
COAX	1

POWER PARAMETERS

Voltage	100-240V ~ 50/60Hz	100-240V ~ 50/60Hz	100-240V ~ 50/60Hz
Max power consumption	250W	280W	350W
Standby power consumption	≤0.5W	≤0.5W	≤0.5W

SIZE & WEIGHT

Bare dimension	1484.60×919.88×87.2mm	1706.76×1027.32×87.31mm	1952.96×1167.77×87.18mm
Packing dimension	1630×220×1050mm	1860*220*1160mm	2120*220*1325mm
Net weight	43±1KG	58±1KG	85±1KG
Gross weight	49.5±1KG	68±1KG	98±1KG



PROMARK INTERACTIVE PANEL

ACCESSORIES

Power cord	x1
Stylus pen	x1
Wall mount	x1
Operation manual	x1

ENVIRONMENTAL FACTORS

Working temperature	0°C-40°C
Working humidity	10%-90%RH